

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Deien

Serial No. 10/548,639

Group Art Unit: [2859]

Filed: 8/26/2003

Examiner: Reis

For: Compound bow rifle sight system

Commissioner for Patents
P.O. Box 1450
Alexandria, VAAMENDMENT AND RESPONSE

Sir:

In response to a call from examiner Reis indicating that the original amendment attached and mailed 8/18/2004 has been lost at the US Patent Office, applicant is sending by facsimile as requested by examiner, a duplicate copy of the original amendment.

Note that the US Patent Office PAIR system shows that the original amendment was received and entered as incoming workflow on 8/18/2004.



Mark Mahley
Agent of Record
36592

Amendments to the specification:

Substitute the enclosed Figure 5 for the original Figure 5 to correct drawing typographical error noted by examiner correcting callout '109' to '119'. A marked up version of the Figure shows the change in red.

On page 9 substitute the following corrected paragraph for the paragraph starting on line 8:

A sight 50 is positioned in and movable along the elongated slot 26. The sight 50 can comprise an elongated threaded member 52 having a first end 54 and a second end 56. The elongated member 52 can extend through the slot 26. A pair of securing members 58 and 58a are threadably coupled to the elongated member 52 for removably securing the elongated member 52 to the first plate 12. The first plate 12 is secured between the securing members 58 and 58a each of which can be a nut. A disc 60 is attached to the first end 54 of the elongated member 52. The disc lies in a plane oriented perpendicular to the plane of the first plate and perpendicular to a line defining the direction of arrow flight to a target not shown. The disc 60 has an edge with a V-shaped groove 62 therein. Alternatively, the disc 60 may have a rectangular shape, or other geometrical shapes in place of the round shape. Of importance is the V-shaped groove 62 which is used for sighting purposes.

Substitute the following 2 corrected paragraphs for the two paragraphs starting on page 11 line 26:

Figure 9 shows the view an archer would have using the present invention if the bow 2 or some aspect of the archer's body is misaligned. In this case the archer's eye is to the right of perfect alignment with the groove 116. Bow 2 position or the archer's head position could cause this condition. With the prior art the archer could have made the shot and even though the pin 209 could have been right on target the shot would have gone to the right of target. But with the present invention the archer is warned that the shot is misaligned but to the right of the front V 116a of the groove. This is now the thickness or distance between the front 116a and back 116b V assures the accuracy of the

BEST AVAILABLE COPY